


19550 URTICA CT-DTO50-AB

Ceiling-mounted spotlight fitting

5905339195500



The Kanlux URTICA decorative holder is distinguished by rich, even brave decors on the ring. The holder requires a well-thought-of combination with interiors where you want to place it. However, the effect generated by it can be really exceptional.

GENERAL DATA:

Colour: patinated brass

Necessity of using self-shielding lamps: yes

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

The product is not suitable to be installed on a normally flammable surface: >35W

The product is not suitable to be covered with a heat-insulating material: yes

Light source included: no

Height [mm]: 24

Diameter [mm]: 90

Assembly hole [mm]: Ø75-80

Wire length [m]: 0.12

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC

Maximum power [W]: max 35

Class of protection against electric shock: III

Light source: MR16

Cap: Gx5,3

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Free cable ends

Wire diameter [mm²]: 0.75

Lighting-fixture angle regulation: in one axis

Lighting-fixture angle regulation [°]: 30

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Number of units per layer on a pallet: 350

Net unit weight [g]: 110

Grammage [g]: 141.4

Length of a unit pack [cm]: 9

19550 URTICA CT-DTO50-AB

Ceiling-mounted spotlight fitting



Width of a unit pack [cm]: 4
Height of a unit pack [cm]: 9
Weight of a cardboard box [kg]: 7.07
Width of a cardboard box [cm]: 20
Height of a cardboard box [cm]: 22
Length of a cardboard box [cm] : 47
Volume of a cardboard box [m³]: 0.02068