

## 22770 CROTO LED-GR-L


Surface-mounted light fitting

5905339227706















Kanlux CROTO is a façade luminaire in graphite colour, characterised by modern design and energy efficiency. Due to the specific shape of the front panel, the luminaire seems to lie flat against the wall. The luminaire perfectly fulfills its function as a decorative lighting, additional stair lighting or illumination of spaces around buildings.

#### **GENERAL DATA:**

**Colour**: grey

Place of assembly: wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,2m

Compatible with a dimmer: no

Length [mm]: 124 Width [mm]: 28 Height [mm]: 125

**Integrated LED light source**: yes

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 1,1

Class of protection against electric shock: ||

**Diode type**: LED SMD **Luminous flux [lm]**: 30

Colour temperature: cold white

Correlated colour temperature [K]: 6500 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 20000

Number of on/off cycles: ≥15000

Ambient temperature range to which the product can be


exposed: -20÷35

Enclosure material: plastic
Protective glass material: PC
Connection type: Bolt terminal block

Range of sections of wires used [mm $^2$ ]:  $0.5 \div 1.5$ 

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IK class: 09 IP class: 65





# 22770 CROTO LED-GR-L

### Surface-mounted light fitting





### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 40

Number of units in the secondary packaging: 1

Number of units in the packaging: 40

Net unit weight [g]: 190 Grammage [g]: 240

Length of a unit pack [cm]: 13.5
Width of a unit pack [cm]: 3.5
Height of a unit pack [cm]: 13.5
Weight of a cardboard box [kg]: 9.6
Width of a cardboard box [cm]: 21
Height of a cardboard box [cm]: 29
Length of a cardboard box [cm]: 56
Volume of a cardboard box [m³]: 0.034104

