

## **29588** AREL LED DO 14W-NW

Downlight fitting

5905339295880













Kanlux AREL LED is a new family of downlights which do not have frame. High tightness class IP65/20 and exceptional, simple, and at the same time surprising design make Kanlux AREL LED fit into each interior. Thanks to the unique structure, the panel is only 9 mm thick - it is the thinnest panel available on the market.

### **GENERAL DATA:**

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

The product is not suitable to be covered with a heat-

insulating material: yes

Height [mm]: 23 Diameter [mm]: 156

Assembly hole [mm]: Ø140 Integrated LED light source: yes

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 14

Class of protection against electric shock: ||

Lampshade material: PMMA

Diode type: LED SMD Luminous flux [lm]: 1300 Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 15000

Number of on/off cycles: ≥30000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 93

Ambient temperature range to which the product can be


exposed: 5÷25

**Enclosure material**: aluminum alloy **Connection type**: Terminal block

Range of sections of wires used [mm<sup>2</sup>]: 0,75-1,5

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

**IP class**: 65/20




We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





# **29588** AREL LED DO 14W-NW

## Downlight fitting





### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50


Number of units in the secondary packaging: 1

Number of units in the packaging: 50

Net unit weight [g]: 220 Grammage [g]: 294.6

Length of a unit pack [cm]: 18.5 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 19

Weight of a cardboard box [kg]: 14.73 Width of a cardboard box [cm]: 38.5 Height of a cardboard box [cm]: 22 Length of a cardboard box [cm]: 78 Volume of a cardboard box [m³]: 0.066066



KANLUX S.A. (kat 29588) AREL LED DO 14W-NW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 29588) AREL LED DO 14W-NW Lamps: 1 x AREL LED DO 14W-NW

