


29602 XLED A60 7W-NW

LED light source

5905339296023




Kanlux XLED combines the best features of traditional bulbs and modern LED light sources. Therefore, we talk about it as the first real LED bulb. A glass bulb in the shape of a traditional bulb and LED diodes placed in such a way so that light can part in all directions, and the angle of light comes to even 320 degrees!

TYPE OF LIGHT SOURCE:**Lighting technology used:** LED**Non-directional or directional light source:** NDLS**Mains or non-mains light source:** MLS**Connected light source (CLS):** no**Colour-tuneable light source:** no**High luminance light source:** no**Anti-glare shield:** no**Dimmable:** no**PRODUCT PARAMETERS:****Colour:** transparent**Compatible with a dimmer:** no**Diameter [mm]:** 60**Mercury content:** no**Rated voltage [V]:** 220-240 AC**Rated frequency [Hz]:** 50/60**Lamp rated current [mA]:** 58**Rated power [W]:** 7**Lampshade material:** glass**Light source:** A60**Diode type:** LED FILAMENT**Colour temperature:** white**Cap:** E27**Rated lamp-service life [h]:** 15000**Number of on/off cycles:** ≥15000**Light source shape:** standardowa**GENERAL PRODUCT PARAMETERS:****Energy consumption in on-mode (kWh/1000h):** 7**Energy efficiency class:** E**Useful luminous flux Φ_{use} [lm]:** 810**Useful luminous flux Φ_{use} [lm]:** in sphere (360°)**Correlated colour temperature [K]:** 4000**On-mode power P_{on} [W]:** 7**Height [mm]:** 105**Width [mm]:** 60**Depth [mm]:** 60**Colour rendering index:** 80

29602 XLED A60 7W-NW

LED light source



Chromaticity coordinates (x): 0.38
Chromaticity coordinates (y): 0.38
Claim of equivalent power [W]: 60

PARAMETERS FOR LED AND OLED LIGHT SOURCES:

R9 colour rendering index value: 8
Survival factor: ≥ 0.9
The lumen maintenance factor: 0.93

PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:

Displacement factor ($\cos \phi$): 0.5
Colour consistency in McAdam ellipses: ≤ 6
LED light source replaces a fluorescent light source without integrated ballast of a particular wattage: Not applicable
Flicker metric (Pst LM): $\leq 1,0$
Stroboscopic effect metric (SVM): $\leq 0,4$

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 10
Number of units in the secondary packaging: 10
Number of units in the packaging: 100
Net unit weight [g]: 34
Grammage [g]: 66
Length of a unit pack [cm]: 6.5
Width of a unit pack [cm]: 6.5
Height of a unit pack [cm]: 12
Weight of a cardboard box [kg]: 6.6
Width of a cardboard box [cm]: 35.5
Height of a cardboard box [cm]: 26.5
Length of a cardboard box [cm]: 69
Volume of a cardboard box [m³]: 0.064912

