


## Facade luminaire

5905339298324











A series of facade Kanlux LART luminaires is a raw and at the same time classic line of facade luminaires in a casing made of aluminium. The external surface of the luminaire is completed in a graphite colour. Kanlux LART look perfect both on a single basis and in combination of several luminaires - subtly complementing light arrangements on terraces or facades of buildings.

#### GENERAL DATA:

Colour: anthracite Place of assembly: wall mounted Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Compatible with a dimmer: no RAL: 7016 Light source included: no Fixture lighting direction: down Length [mm]: 110 Width [mm]: 180 Height [mm]: 185

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 60 Class of protection against electric shock: | Lampshade material: glass Light source: GLS/CFL/LED **Cap**: E27 Ambient temperature range to which the product can be **exposed**: -20÷35 Enclosure material: aluminum alloy Panel/frame material: aluminum alloy Basic fixture material: aluminum alloy Protective glass material: Tempered glass Connection type: Bolt terminal block Range of sections of wires used [mm<sup>2</sup>]: 0,5÷1,5 **IP class**: 54

#### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12 Number of units in the secondary packaging: 1 Number of units in the packaging: 12



# Facade luminaire



Net unit weight [g]: 1002 Grammage [g]: 1158.33 Length of a unit pack [cm]: 18.5 Width of a unit pack [cm]: 11.5 Height of a unit pack [cm]: 19.5 Weight of a cardboard box [kg]: 13.89996 Width of a cardboard box [cm]: 37 Height of a cardboard box [cm]: 41 Length of a cardboard box [cm]: 39 Volume of a cardboard box [m<sup>3</sup>]: 0.059163

