


## 33514 XLED A60 M 7W-WW

LED light source

5905339335142



Exceptional, decorative bulbs Kanlux XLED MIRROR provide decorative silver light. Part of the bubble is a mirror coating that will blend in perfectly as an addition to modern designs. The light in Kanlux XLED MIRROR is reflected upwards with a reflective layer, providing less direct light and creating a cosy atmosphere. It is perfect for lamps with an exposed bulb as an additional decoration or for lamps with a lampshade, where we can achieve the effect of subdued, romantic light.

### GENERAL DATA:

**Lamp designed for decorative lighting:** Not applicable  
**Compatible with a dimmer:** no  
**Height [mm]:** 108  
**Diameter [mm]:** 60  
**Depth [mm]:** 60  
**Mercury content:** no

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Material:** glass  
**Light source:** A60  
**Diode type:** LED FILAMENT  
**Total rated luminous flux [lm]:** 680  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 680  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)  
**Colour temperature:** Warm white  
**Correlated colour temperature [K]:** 2700  
**Colour consistency in McAdam ellipses:**  $\leq 6$   
**Colour rendering index:** 80  
**Cap:** E27  
**Rated lamp-service life [h]:** 15000  
**Number of on/off cycles:**  $\geq 15000$   
**Rated beam angle [°]:** 150  
**Rated light level [°]:** 150  
**Lamp rated current [mA]:** 40  
**Annual power consumption [kWh/1000h]:** 7  
**Ignition time [s]:**  $\leq 0,5$   
**Lamp-heating time to 60% of the full luminous flux [s]:** Negligible  
**Lamp-heating time to 95% [s]:**  $< 2$   
**Lamp premature-failure indicator:**  $< 5\%$  po 1000h  
**Lamp service life factor after the period of 6000h [%]:**

## 33514 XLED A60 M 7W-WW

LED light source



≥90

**Luminous flux retention factor at the end of rated service life [%]:** ≥70

**Luminous flux retention factor after the period of 6000h [%]:** ≥80

**Declaration of equality in power rating [W]:** 52

**Light source shape:** standard

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 10

**Number of units in the secondary packaging:** 10

**Number of units in the packaging:** 100

**Net unit weight [g]:** 36

**Grammage [g]:** 60

**Length of a unit pack [cm]:** 6.5

**Width of a unit pack [cm]:** 6.5

**Height of a unit pack [cm]:** 12

**Weight of a cardboard box [kg]:** 6

**Width of a cardboard box [cm]:** 35.5

**Height of a cardboard box [cm]:** 27.5

**Length of a cardboard box [cm]:** 68.5

**Volume of a cardboard box [m<sup>3</sup>]:** 0.066873

