


Facade luminaire

5905339070807



IP
54



Kanlux BART EL is a façade luminaire which perfectly blends into a modern building and constructions of a more classic style. The rating of tightness (IP54) of Kanlux BART EL luminaire ensures resistance to weather conditions.

GENERAL DATA:

Colour: grey

Place of assembly: wall mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Light source included: no

Fixture lighting direction: up and down

Length [mm]: 85

Width [mm]: 115

Height [mm]: 143

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 2 x max 35

Class of protection against electric shock: I

Light source: PAR16

Cap: GU10

Ambient temperature range to which the product can be exposed: -20÷35

Enclosure material: aluminum alloy

Protective glass material: Tempered glass

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

IP class: 54

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 18

Number of units in the packaging: 18

Net unit weight [g]: 510

Grammage [g]: 605.56

Length of a unit pack [cm]: 12.5

Width of a unit pack [cm]: 9

Height of a unit pack [cm]: 15.5

Weight of a cardboard box [kg]: 10.90008

Width of a cardboard box [cm]: 29

Height of a cardboard box [cm]: 39

Length of a cardboard box [cm]: 32

Volume of a cardboard box [m³]: 0.036192

Facade luminaire

