


In-ground fixture

5905339072818



Kanlux ROGER DL is a ground-recessed luminaire with a built-in LED module. The specific shape of the shade distributes light evenly, which produces a unique light effect. The luminaire has a very high rating of tightness (IP66) and resistance to mechanical damage (IK09).

GENERAL DATA:

Colour: grey
Place of assembly: In the ground
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,1m
Compatible with a dimmer: no
Fixture lighting direction: horizontal
Height [mm]: 74
Diameter [mm]: 100
Wire length [m]: 0.3
Number of chokes: 1
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 1
Class of protection against electric shock: I
Diode type: LED DIP
Colour temperature: cold white
Correlated colour temperature [K]: 6000-6500
Service life [h]: 20000
Ambient temperature range to which the product can be exposed: -20÷35
Enclosure material: steel
Panel/frame material: aluminum alloy
Protective glass material: plastic
Connection type: Free cable ends
Wire diameter [mm²]: 0,75
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
Permissible static pressure [kN]: 5
IK class: 09
IP class: 66

In-ground fixture



LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 24
Number of units in the secondary packaging: 1
Number of units in the packaging: 24
Net unit weight [g]: 270
Grammage [g]: 333.33
Length of a unit pack [cm]: 10
Width of a unit pack [cm]: 10.5
Height of a unit pack [cm]: 9
Weight of a cardboard box [kg]: 7.99992
Width of a cardboard box [cm]: 22
Height of a cardboard box [cm]: 37
Length of a cardboard box [cm]: 32
Volume of a cardboard box [m³]: 0.026048

ADDITIONAL INFORMATION:

- Junction box included

KANLUX S.A. (kat 7281) ROGER DL-2LED6 / Krzywa rozsytu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 7281) ROGER DL-2LED6
Lampy: 1 x ROGER DL-2LED6

