

## NOCTIS LUX 2 floodlight




CE

Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>850 lm (120°)</b>	Colour of light	<b>WW</b>
Beam angle	<b>100 °</b>	Degree of protection (IP)	<b>IP65</b>




See more on dedicated page [➔](#)



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029037WW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	850 lm (120°)
Luminous flux**	810/850 lm (360°)
Lamp efficacy	81 lm/W
Colour of light	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	83x104x23 mm
Weight	0.19 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Number of pieces on the packaging	12 pcs.
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux