

NOCTIS LUX 2 floodlight




CE

Power	30 W	Voltage	230 V
Luminous flux*	2740 lm (120°)	Colour of light	WW
Beam angle	100 °	Degree of protection (IP)	IP65



See more on dedicated page [➔](#)



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029039WW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2740 lm (120°)
Luminous flux**	2600/2740 lm (360°)
Lamp efficacy	87 lm/W
Colour of light	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	120x160x28 mm
Weight	0.4 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Number of pieces on the packaging	20 pcs.
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux