


LED STRIP 120LED/M 1M • 12V • 9.6W • YELLOW • IP20 • 110LM • 8MM



9.6W /m
12V DC
2.5cm cutting length
3oz 8mm FPC
30m reel for IP20, 10m for IP66 / IP68
Warranty 3 years

High quality colour LED strip for professional use. Two layers of PCB with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE.

Specification

Parameter	Value
Symbol	SCA-120-Y
EAN13	5901289755719
ETIM CLASS	Light ribbon-/hose/-strip
Socket	wires
Model	Tape
Mains or non-mains	NMLS
Dimmable	yes
Power [W]	9.6
Colour of light	Yellow
Number of nodes per meter	120
Degree of protection	IP20
Suitable for use	
cutting length [cm]	2.5
Voltage [V]	12
Voltage type	DC
Luminous flux [lm]	110
Standby power consumption [W]	0
Beam angle [°]	120
Correspondence beam angle	Sphere 360°
Non-directional or directional	Non-directional light source NDLS
Survival factor	0.9
Lumen maintenance factor	0.96

With Self-adhesive	yes
Min. number of switching cycles	50000
Rated life time L70/B50 at 25 °C [h]	35000
Colour-tuneable light source (CTLS)	yes
Connected light source (CLS)	yes
High-luminance light source (HLLS)	yes
Anti-glare shield	yes
Width [mm]	8
Height/depth [mm]	1.4

Dimensions

