


LED STRIP 120LED/M 1M • 24V • 22W • RGB • IP20 • 815LM • 10MM

24W /m  
24V DC  
5.0cm cutting length  
3oz 10mm FPC  
50000h L70 lifespan  
10m reel, 10m dla IP66/IP68  
Warranty 3 years

Multicolour LED strip for professional use in decorative lighting, one LED with 3-chips. Two layers of PCB with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE.

## Specification

Parameter	Value
Symbol	SPF-120-RGB-24
EAN13	5901289754040
ETIM CLASS	Light ribbon-/hose/-strip
Socket	wires
Model	Tape
Mains or non-mains	NMLS
Dimmable	yes
Power [W]	22
Colour of light	RGB
Number of nodes per meter	120
Degree of protection	IP20
Suitable for use	
cutting length [cm]	5
Voltage [V]	24
Voltage type	DC
Luminous flux [lm]	815
Standby power consumption [W]	0
Beam angle [°]	120
Correspondence beam angle	Sphere 360°
Non-directional or directional	Non-directional light source NDLS
Survival factor	0.9
Lumen maintenance factor	0.96

With Self-adhesive	yes
Min. number of switching cycles	50000
Rated life time L70/B50 at 25 °C [h]	35000
Colour-tuneable light source (CTLS)	yes
Connected light source (CLS)	yes
High-luminance light source (HLLS)	yes
Anti-glare shield	yes
Width [mm]	10
Height/depth [mm]	2