

## **32940** BENO 18W NW-O-W

Ceiling-mounted LED light fitting

5905339329400























Kanlux BENO luminaries that's unique design and unique light effect. They were created on the basis of individual order of Kanlux, and their designs were registered by us at the patent office. Kanlux BENO LED also provides high weather resistance (IP54), quick and easy installation on the ceiling or wall, and Beno is equipped with the adjustable movement sensor(in versions -SE). Kanlux BENO LED is a multifunctional fitting, which due to its design and its technical aspects, we can apply practically anywhere.

### **GENERAL DATA:**

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Height [mm]: 55 Diameter [mm]: 220 Mercury content: no

Integrated LED light source: yes

#### TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 18

Class of protection against electric shock: ||

Lampshade material: plastic

Diode type: LED SMD

Luminous flux of the light fitting [lm]: 1550

Useful luminous flux of the light source **Φuse** [lm]: 2400 Useful luminous flux of the light source **Φuse** [lm]: in

sphere (360°)

Colour temperature: white

Correlated colour temperature [K]: 4000 Colour consistency in McAdam ellipses: ≤6

Colour rendering index: 80 Service life [h]: 20000

Luminous-flux-retention factor at the end of rated

service life: L70B50

Number of on/off cycles: ≥20000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 86

Ambient temperature range to which the product can be

exposed: -15÷35

Date of issue: 16.11.2022, 06:21


We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.






# **32940** BENO 18W NW-O-W

### Ceiling-mounted LED light fitting





Enclosure material: plastic

Connection type: Self-clamping block

Range of sections of wires used [mm<sup>2</sup>]:  $0.5 \div 1.5$ 

Lamp-heating time [s]:  $\leq 1$ Lamp-ignition time [s]:  $\leq 0.5$ 

IP class: 54

#### LOGISTIC DATA:

Packaging method: 10

Number of units in the secondary packaging: 1


Number of units in the packaging: 10

Net unit weight [g]: 420 Grammage [g]: 577

Length of a unit pack [cm]: 22.5 Width of a unit pack [cm]: 6 Height of a unit pack [cm]: 23

Weight of a cardboard box [kg]: 5.77 Width of a cardboard box [cm]: 32.5 Height of a cardboard box [cm]: 25 Length of a cardboard box [cm]: 47

Volume of a cardboard box [m³]: 0.038188



KANLUX S.A. (kat 32940) BENO 18W NW-O-W / LDC (Polar)

Luminaire: KANLUX S.A. (kat 32940) BENO 18W NW-O-W Lamps: 1 x BENO 18W NW

